



## DIGITAL DOSING up to 940 l/h

By popular demand, Grundfos has applied innovative technology to expand the Digital Dosing pump range, allowing it to handle liquids in much larger quantities. With just four models the new DME range can cover the range from 75 ml/h to 940 l/h. Perfect for large water and wastewater treatment plants, textile industries, pulp and paper industries, and many other demanding applications, the new, large DME pumps bring the benefits of Digital Dosing to a new circle of users worldwide.

### Familiar Digital Dosing benefits

The 60 – 940 l/h pump range has all the benefits of the highly acclaimed smaller Digital Dosing range, making exact dosing easier than ever.

### Easy-to-use digital user interface

The simple display allows everyone to be their own dosing specialist. With just a few buttons, you can navigate the straightforward menus to use the impressive range of standard control features – including pulse, analog, timer, batch, and anti-cavitation control – as well as simple calibration and much more.



### Turndown ratio 1:800

With a turndown ratio ten times better than that of traditional equipment, the large Digital Dosing pumps give you greater flexibility and accuracy than ever. Only four pump sizes cover the range from 75 ml/h - 940 l/h.

### Full stroke length at all times

Grundfos is the only pump manufacturer to use a full stroke length every time. The strokes are carefully timed, ensuring even concentration in the system and optimal priming throughout the entire operating range.

### Brushless DC motor ensures full control

The ingenious design of the large Digital Dosing pumps eliminates the need for a servo motor/frequency converter and ensures smooth and gentle dosing.

### Anti-cavitation

Turndown of the suction stroke to 75%, 50% or 25% of the maximum speed ensuring optimal priming and displacement of even the most difficult liquids.

### Fieldbus communication available

Available with Profibus or Genibus interface.

### Overload protection

Built-in overload protection monitors pump counter pressure and protects against exceptionally high pressure loads.

### Switch-mode power supply

The switch-mode power supply ensures that Grundfos Digital Dosing pumps can be used worldwide within the 100–240VAC – 50/60Hz range.

### Several material variants

The DME pump heads are available in stainless steel, PVDF, and environmentally friendly, cost-efficient polypropylene.

### Dimensions (mm)

	DME 60-10	DME 150-4	DME 375-10	DME 940-4	
A	176	176	238	238	
B	198	198	218	218	
C	331	345	471	496	
D	284	284	364	364	
E	180	180	230	230	
F	444	444	540	539	
G	41	28	31	6	
H	74	74	95	95	
I	187	187	246	246	

### Product range and performance data

Pump type		DME 60-10	DME 150-4	DME 375-10	DME 940-4
Max. capacity at max. pressure	[l/h]	60	150	376	940
Min. capacity	[l/h]	0.075	0.188	0.47	1.18
Max. pressure	[bar]	10	4	10	4
Setting range		1:800			
Stroke frequency	[min <sup>-1</sup> ]	160			
Power supply	[V], [Hz]	1×100-240V, 50-60 Hz			
Accuracy	[%]	±1% repeatability			
Pumphead material		PP, PVDF, stainless steel			
Suction lift	[m]	4			
Viscosity	[mPa]	3000			

### Performance range

