# **PFOS & PFOA REDUCTION**

**PFOS & PFOA REDUCTION** 

PRO SERIES, DROP-IN CARTRIDGE

Per- and Polyfluoroalkyl substances (PFAS's) are fluorinated organic chemicals that are sometimes called "forever chemicals" because they do not break down naturally over time. Per and Poly Fluorinated compounds have been used in every day items such as food packaging, protective coating's and clothing. These emerging contaminants found their way into the water supply. PFAS's have a tendency to bioaccumulate in the blood and organs of human beings and animals.

Aries PFOS & PFOA reduction cartridges utilize a high purity strong base anion resin exhibiting an unusually high preference for multiple PFAS compounds. The AF-10-3612 filter components are selective for a wide variety of Per and Poly Fluorinated compounds including; PFOS, PFOA, PFNA, PFHpA and PFHxS.

### **HIGHLIGHTS**

- Highest capacity media for PFOS & PFOA removal
- Also removes other Per and Poly fluorinated compounds
- Fits standard residential & industrial sized housings
- Oversized cartridge for maximum media fill
- Lot control traceability
- Made in the USA



### **APPLICATIONS**

- POU
- Drinking Water
- Post RO

#### **SPECIFICATIONS**

- Nominal Rating of 25µ
- Max Pressure of 125 psi (850 kPa)
- Max Temperature 100°F (38 °C)

Revision 2.3



ISO 9001: 2015 CERTIFIED





DIMENSIONS	MAX FLOW		CAPACITY*	PART NUMBER
	gpm	lpm	Gallons	
2.5 x 10 in. (Slim Line)	0.10	0.38	500	AF-10-3612
2.5 x 20 in. (Slim Line)	0.15	0.58	1000	AF-20-3612
4.5 x 10 in. (Big Blue)	0.20	0.76	1100	AF-10-3612-BB
4.5 x 20 in. (Big Blue)	0.50	1.89	1600	AF-20-3612-BB
2 x 12 in. (Quick Connect)	0.05	0.19	175	IF-12-3612

<sup>\*</sup>Capacity measured to 90% removal based on maximum industry standards.

## **CHALLENGE INLET WATER ANALYSIS**

	CONCENTRATION	UNITS
PFOS	1225	ppt
PFOA	563	ppt
Sulfate	224	ppm
Chloride	117	ppm
Alkalinity	218	ppm













