

CLACK WS1.5PEE

WS1.5PEE

WATER SPECIALIST CONTROL VALVE



Inlet/Outlet Fitting Kit Included

- 1.5" top mount control valve suited for mid-size commercial/industrial applications
- Glass filled composite
- Economical plastic optional meter assembly
- Service flow rate of 60 gpm, backwash 43 gpm
- Upflow/downflow brining field convertible
- Solid state microprocessor with easy access front panel settings
- Front panel display for time of day, days until next regeneration, volume remaining, current flow rate and total volume used (Totalizer)
- Four methods to initiate regeneration; meter immediate, meter delayed, time clock delayed or pressure differential
- Optional double backwash feature offers optimum regeneration, cleaning ability and efficiency
- Fully adjustable cycle times with 6-cycle control delivers controlled backwash, downflow brining or upflow brining, slow rinse, second backwash, fast rinse, refill and downflow service
- Coin cell lithium battery backup for time of day up to 8 hours
- Level VI 15-volt output DC power supply provides safe and easy installation
- Post treated water regenerant refill
- Days override feature; 1 – 28 days available
- Patented one piece expanding seal spacer stack assembly U.S. Patent 6,402,944
- Patented linearly reciprocating piston operation U.S. Patent 6,444,127
- Reliable and proven DC drive

DWC
DUFF WATER CONDITIONING
Products for Quality Water

est. 1947
DUFF co.



201 E Lafayette St
Norristown, PA 19401



610-275-4453



duffco.com



info@duffco.com

WATER SPECIALIST 1.5" PLASTIC EE CONTROL SPECS

Inlet/Outlet (1)	1.5" Male NPT
Cycles	Up to 6
Valve Material	Glass filled composite
Regeneration	Downflow / Upflow

CONTROL VALVE FLOW RATES

Service @15 psi drop (includes meter).....	60 gpm
Backwash @ 25 psi drop	43 gpm

OPERATING PRESSURES

Minimum/Maximum	20 psi – 125 psi
-----------------------	------------------

OPERATING TEMPERATURES

Minimum/Maximum	40° – 110° F
-----------------------	--------------

DIMENSIONS & WEIGHT

Distributor Pilot	
Valve bodies with 1.5" Female NPT Inlet & Outlet	1.90" OD (1.5" NPS)
Drain Line Connection	1" Male NPT Elbow
Brine Line Connection	½" OD Poly Tube Compression
Mounting Base	4" - 8 UN
Height From Top Of Tank	10.75"
Shipping Weight.....	XX lbs.

ELECTRICAL SPECIFICATIONS

POWER SUPPLY

	<u>U.S.</u>	<u>International</u>
Supply Voltage	100VAC to 120VAC	200VAC to 240VAC
Supply Frequency	50/60 Hz	50/60 Hz
Output Voltage	15VDC	15VDC
Output Current	500 mA	500 mA

TANK APPLICATIONS

Water Softener	12" – 24" diameter
Water Filter	12" – 24" diameter

CYCLES OF OPERATION

Cycle	<u>Softener</u>	<u>Filter</u>
	Range of time in minutes	
1. Backwash 1 st (upflow)	1-95	Backwash 1-95
2. Regenerate Draw/Slow Rinse (downflow)	1-180	
3. Backwash 2 nd (upflow).....	1-95	
4. Fast Rinse (downflow)	1-95	Rinse 1-95
5. Regenerant Refill (in service with treated water).....	0.1-99.0 or off	
6. Service (downflow)		

Options: Backwash Filter, Weather Cover

Compatible with the following typical concentrations of regenerants or chemicals: Sodium chloride, potassium chloride, potassium permanganate, sodium bisulfite, chlorine and chloramines

1. See Distributor Pilot.

2. Filter tank size calculated @ 10 gpm of backwash per square foot of bed area