

FLECK 2900S SPECS

FLECK 2900s 2-INCH CONTROL VALVE



DUFF WATER CONDITIONING
Products for Quality Water

MADE IN THE USA
OF FOREIGN & DOMESTIC PARTS



FEATURES/BENEFITS

Lead-free brass valve body for superior strength and durability

Continuous service flow rate of 106 GPM with a backwash of 36 GPM

Backwash capability accommodates softener tanks up to 36" and filter up to 24" in diameter

Fully adjustable 3- or 5-cycle control for efficient and reliable water treatment system

Designed for single or multiple tank systems

Environmental protective cover for water resistance, corrosion resistance, and UV stability

Time-tested, hydraulically-balanced piston for service and regeneration

OPTIONS

Filter or softener control valves

Downflow co-current or upflow counter-current regeneration

No hard water bypass piston

Brine cam auxiliary switch

Electromechanical timer auxiliary switch

Hot water

Treated water regeneration

Versatile top or side mount

Electromechanical 7- or 12-day time clock, meter delayed, or meter immediate regeneration

NXT2 - Network up to 8 valves for multi-system control. Improved display (OLED) allows for easy viewing. Multivalve system settings can be pushed from one controller to expedite setup.

SXT- Large LCD display and user-selectable time clock or metered function; usable for filtration and softener systems.

XT- Offers a two-line, 16 character LCD backlit display for easy entering of master and user programming as well as view of diagnostics.

Electromechanical Timer- Simple to adjust and easy to service with quick access to all internal components.

VALVE SPECIFICATIONS

Valve Material	Lead-free brass*
Inlet/Outlet	2" NPTF/BSPF
Cycles	5



TESTED and CERTIFIED by the WQA to NSF/ANSI Standard 61 Section 8 Material Safety Only.



TESTED and CERTIFIED by the WQA to NSF/ANSI Standard 372 for Lead Free Compliance.



UL recognized to 979



Restriction of Hazardous Substance Compliant

est. 1947



201 E Lafayette St
Norristown, PA 19401



610-275-4453



duffco.com



info@duffco.com

FLOW RATES (50 PSI INLET) – VALVE ALONE

Continuous 15 psi drop	106 GPM (24.1 m ³ /h)
Peak 25 psi drop	140 GPM (31.8 m ³ /h)
Cv flow at 1 psi drop	27.5
Max. Backwash 25 psi drop	36 GPM (8.2 m ³ /h)

REGENERATION

Downflow/Upflow	Both
Adjustable Cycles	Yes
Time Available	
Electromechanical:	0 - 164 min/regeneration
NXT2:	0 - 240 min/cycle
XT:	0 - 240 min/cycle

METER INFORMATION

Meter Accuracy	
2" Paddle:	3 - 150 GPM ± 5% (.68 - 34 m ³ /h)
Meter Capacity Range	
2" Standard:	1,250 - 21,250 gal (5 - 75 m ³)
2" Extended:	6,250 - 106,250 gal (24 - 375 m ³)
NXT2:	1 - 9,999,999 gal (0 - 37,854 m ³)
XT:	1,000 - 9,900,000 gal (3.8 - 37,854 m ³)

DIMENSIONS

Distributor Pilot	1..9" O.D. (50 mm)
Drain Line	1" NPTM
Brine Valve	
1600 or 1650:	3/8"
1700 or 1710	1/2"
Injector System	1600 or 1700
Mounting Base	4" - 8 UN

Height from Top of Tank	12" (305 mm)
Riser Tube Diameter	1-1/2" (38 mm)
Riser Height	1/4" Below top of tank

TYPICAL APPLICATIONS

Water Softener	14 - 36" diameter
Filter	14 - 24" diameter based on 10 GPM/ft ²

ADDITIONAL INFORMATION

Electrical Rating	24/110/220V; 50/60 Hz
Estimated Shipping Weight	
Time Clock:	33 lbs
Metered Valve:	40 lbs
Pressure	
Hydrostatic:	300 psi (20 bar)
Working:	20 - 125 psi (1.4 - 8.5 bar)
Temperature	
Cold Water Valve:	34 - 110°F (1 - 43°C)
Hot Water Valve:	34 - 180°F (1 - 82°C)
Time Clock, 1600 Brine System	
Hot Water Valve:	34 - 150°F (1 - 66°C)
1700 Brine System	

*As defined in the U.S. EPA Safe Drinking Water Act; the product also meets California Proposition 65 Standards for lead-free brass.

Pentair trademarks and logos are owned by Pentair plc or its affiliates. Third party registered and unregistered trademarks and logos are the property of their respective owners.

© 2020 Pentair Residential Filtration, LLC. All rights reserved.

40738 REV F AP20



201 E Lafayette St
Norristown, PA 19401



610-275-4453



duffco.com



info@duffco.com