

FLECK 56SXT SPECS

FLECK 56SXT HIGH PERFORMANCE CONTROL VALVE

MULTIPLE OPTIONS FOR FILTER AND SOFTENER APPLICATIONS



FEATURES/BENEFITS

Continuous service flow rate of 20 GPM with a backwash of 7 GPM

Backwash capability accommodates softener tanks up to 12" and filters up to 10" in diameter

Fully adjustable 3- or 5-cycle control for efficient and reliable water treatment system

Super capacitor for keeping time of day during power outage

Time-tested, hydraulically-balanced piston for service and regeneration

Diagnostics for historical valve performance

LCD display alternates between time of day, volume remaining or days until regeneration

Programming stored in memory and will not be lost due to power outages

OPTIONS

Filter or softener control valves

Downflow regeneration

Brine cam auxiliary switch

Plumbing connections in 3/4" or 1" NPT, BSP, and sweat

Fiber-reinforced polymer or stainless steel bypass valve

Programmable regeneration types for increased flexibility

Downflow double backwash cam for reduced hardness leakage

SXT - Large LCD display and user-selectable time clock or metered function; usable for filtration and softener systems



TESTED and CERTIFIED by the WQA to NSF/ANSI Standard 44 for Water Softener Performance.



TESTED and CERTIFIED by the WQA to NSF/ANSI Standard 372 for Lead Free Compliance.



Restriction of Hazardous Substance Compliant

est. 1947

DUFFco.



201 E Lafayette St
Norristown, PA 19401



610-275-4453



duffco.com



info@duffco.com

VALVE SPECIFICATIONS

Valve Material	Fiber-reinforced polymer
Inlet/Outlet	3/4" or 1" NPT/BSP/ Sweat
Cycles	5

FLOW RATES (50 PSI INLET) – VALVE ALONE

Continuous 15 psi drop	20 GPM (4.5 m ³ /h)
Peak 25 psi drop	26 GPM (5.9 m ³ /h)
Cv flow at 1 psi drop	5.0
Max. Backwash 25 psi drop	7 GPM (1.6 m ³ /h)

REGENERATION

Downflow/Upflow	Both
Adjustable Cycles	Yes
Time Available SXT:	0 - 199 min/cycle

METER INFORMATION

Meter Accuracy 3/4" Paddle/Turbine:	0.25 - 15 GPM ± 5% (0.06 - 3 m ³ /h)
Meter Capacity Range SXT:	1 - 999,900 gal (0 - 3,785 m ³)

DIMENSIONS

Distributor Pilot	0.8125" or 1.05" O.D. (26.7 mm)
Drain Line	1/2" NPTF
Brine Valve 1600:	3/8"
Injector System	1600
Mounting Base	2.5" - 8 NPSM
Height from Top of Tank	7.5" (190 mm)
Riser Tube Diameter	3/4" (19 mm)
Riser Height	Flush with top of tank

TYPICAL APPLICATIONS

Water Softener	6 - 12" diameter
Filters	8 - 10" diameter based on 10 GPM/ft ²

ADDITIONAL INFORMATION

Electrical Rating	24V 50/60 Hz
Max. VA	8.4
Estimated Shipping Weight	
Time Clock:	6 lbs
Metered Valve:	7 lbs
Pressure	
Hydrostatic:	300 psi (20 bar)
Working:	20 - 125 psi (1.4 - 8.5 bar)
Temperature	
Cold Water Valve:	34 - 110°F (1 - 43°C)

© 2017 Pentair Residential Filtration, LLC. All rights reserved.

§For a detailed list of where Pentair trademarks are registered, please visit waterpurification.pentair.com/brands. Pentair trademarks and logos are owned by Pentair plc or its affiliates. Third party registered and unregistered trademarks and logos are the property of their respective owners.

42749 REV F JL17

