

est. 1947

DUFFco.

When you need it now... or don't know how

PORTABLE EXCHANGE TANKS

**The portable,
easy-to-change
vessel for light
commercial water
treatment applications.**

Eliminate downtime and hassles with Structural Exchange tanks. Our Noryl exchange head, 4.5" threaded openings, and standard disconnects are designed to operate with your existing system.

Changeover is quick, easy, and affordable. Structural Exchange tanks come with a 5-year exclusive warranty.

Material of construction

*Inner shell material:
Polyethylene*

Operating parameters

*Maximum operating pressure:
150 psi*

*Maximum operating temperature:
120° F*

Design parameters – Pentair

*Safety factor:
4:1 (Minimum burst at 600 psi)*

*Cycle test:
250,000 cycles without leakage*

Design parameters – NSF

*Safety factor:
4:1 (Minimum burst at 600 psi)*

*Cycle test:
100,000 cycles without leakage*



Structural Exclusives!

- *Noryl manifold is 30% stronger than conventional ABS*
- *No steel bands required*
- *High performance inner polyethylene liner provides impact and corrosion resistance*

CALL 610-275-4453





DUFFCO.COM

INFO@DUFFCO.COM

12" Tanks	Tank Part No.	Tank Size	Top Opening		
	32127	12 x 52	4.5" T BTRS		
12" Tank Kits	Kit Part No.	Tank Size	Fill Port	Flow	No. Segments/ Basket
	14819	12 x 52	1-7/8"	Full Flow	12
	14820	12 x 52	1-7/8"	Peak Flow	19
	14823	12 x 52	1"	Full Flow	12
	14824	12 x 52	1"	Peak Flow	19
14" Tanks	Tank Part No.	Tank Size	Top Opening		
	32006	14 x 47	4.5" T BTRS		
14" Tank Kits	Kit Part No.	Tank Size	Fill Port	Flow	No. Segments/ Basket
	14817	14 x 47	1-7/8"	Full Flow	12
	14818	14 x 47	1-7/8"	Peak Flow	19
	14821	14 x 47	1"	Full Flow	12
	14822	14 x 47	1"	Peak Flow	19



Accessories and Replacement Parts





Should not be used as the primary indicator for critical or medical applications.

SPECIFICATIONS

Available Thresholds: 10K to 1 Meg ohm·cm
 Accuracy: ± 15%
 Thread: ½" NPT with o-ring or ¾" NPT
 Weight: 200 gm
 Housing Material: ABS Black
 Electrode Material: Monel
 Sampling Frequency: 150 Hz
 Sampling Voltage: 2.2 volts peak at threshold
 Supply Voltage: 120 VAC
 Supply Frequency: 60 Hz
 Output Voltage: 9 VDC
 Output Current: 200 mA
 Cord Length: 9 feet
 Working PSI: 125 psi
 Maximum Temperature: 100°F
 Typical DC Current: 35mA
 Typical Lumen Output: Green 80 mcd
 Red 200 mcd



The square wave Resilite is an economical method of monitoring water quality via conductivity.

The bright red or green visual output is easy to read. The monitoring is simple; the green light indicates the water conductivity is below the threshold value; the red light indicates that it is above.

The LED output and solid state circuitry will outlast conventional neon lamps.

Values from 10,000 ohm·cm to 1 Meg ohm·cm.

RESISTIVITY (ohm·cm)	CONDUCTIVITY (µS/cm)	~ TDS ± 15% (ppm)
1 MEG	1	.50
500K	2	1.0
200K	5	2.5
50K	20	10
20K	50	24
10K	100	48

Stock thread sizes are ½" NPT and ¾" NPT. Electrodes must be fully immersed at all times. Avoid installation in air pockets or where air pockets can form.



ACCESSORIES

The **RA201 890 Plastic Distributor Head** is designed for installation of a 1/2" Resilite in single in-out applications on deionizers. The threaded opening on the outlet side places the monitor electrodes into the water flow for greater accuracy. This economical head is molded of rugged plastic, fits a standard 2 1/2" - 8 tank opening, adapts to a 1 3/16" riser and has 3/4" NPT inlet and outlet for straight line installation.

The **RA102 Plastic Tee** is designed for in-line installation of a 1/2" Resilite. The threaded center opening places the monitor electrodes into the water flow for greater accuracy. The inlet and outlet of the tee are 3/4" socket joints (solvent weld).

ORDER INFORMATION

RESILITES [®]		
ORDER NUMBER	DESCRIPTION	QTY PER CTN
R7031-10K	120V 10K ohm · cm 1/2"	1
R7031-20K	120V 20K ohm · cm 1/2"	1
R7031-50K	120V 50K ohm · cm 1/2"	1
R7031-200K	120V 200K ohm · cm 1/2"	1
R7031-500K	120V 500K ohm · cm 1/2"	1
R7031-1MEG	120V 1 Meg ohm · cm 1/2"	1
R7046-10K	120V 10K ohm · cm 3/4"	1
R7046-20K	120V 20K ohm · cm 3/4"	1
R7046-50K	120V 50K ohm · cm 3/4"	1
R7046-200K	120V 200K ohm · cm 3/4"	1
R7046-500K	120V 500K ohm · cm 3/4"	1
R7046-1MEG	120V 1 Meg ohm · cm 3/4"	1

ACCESSORIES		
ORDER NUMBER	DESCRIPTION	QTY PER CTN
R7009	RA201 890 Plastic Head w/Adaptor	1
R7011	RA102 Plastic Tee	1

GENERAL INFORMATION:

The Resilite monitor requires that the water be flowing to use indicator light. Ions tend to migrate to the testing cell and affect the reading if the water is not flowing.

Should not be used as the primary indicator for critical or medical applications.